

## AMENDMENTS TO THE CLAIMS

This listing of Claims shall replace all prior versions, and listings, of claims in the application:

### LISTING OF CLAIMS:

1. (Previously Presented) An input detection system for an electronic device comprising:

a first display component;

a second display component disposed above said first display component;

a sensor component operable to detect an indication in proximity to but not in contact with a surface of said electronic device and wherein said sensor is operable to differentiate between a first height and a second height of said indication above said second display component; and

a control circuit coupled to said sensor component and operable to register said indication as an input to said electronic device at one of said first height and said second height, wherein an input at said first height corresponds to said first display component activated by said control circuit, and wherein an input at said second height corresponds to said second display component activated by said control circuit.

2. (Original) The input detection system as recited in Claim 1, wherein said sensor component is a capacitive sensor.

3. (Previously Presented) The input detection system as recited in Claim 1, wherein said sensor component is further operable to detect said electronic device being handled and said control system, responsive to said handling, for actuating said electronic device.

4. (Original) The input detection system as recited in Claim 1, wherein said sensor component is an inductive sensor.

5-7. (Cancelled)

8. (Previously Presented) The input detection system as recited in Claim 1, wherein said control circuit is operable to detect when said cover is in said closed position and in an open position and is further operable to alter a detection threshold of said sensor component when said cover is in said open position.

9. (Original) The input detection system as recited in Claim 8, wherein said sensor component, responsive to said altered detection threshold, detects an indication above said second display component and said control system registers said indication as an input to said electronic device.

10. (Previously Presented) The input detection system as recited in Claim 1, wherein said cover further comprises:

a second sensor component operable to detect an indication in proximity to but not in contact with the surface of said second sensor component, wherein said indication is registered as an input to said electronic device.

11. (Previously Presented) An input detection system for an electronic device comprising:

a first display component;

a second display component disposed above said first display component;

a capacitive sensor component operable to detect an indication in proximity to but not in contact with a surface of said electronic device and wherein said capacitive sensor component is operable to differentiate between a first height and a second height of said indication above said second display component; and

a control circuit coupled to said capacitive sensor component and operable to register said indication as an input to said electronic device at one of said first height and said second height, wherein an input at said first height corresponds to said first display component activated by said control circuit, and wherein an input at said second height corresponds to said second display component activated by said control circuit.

12-14. (Cancelled)

15. (Previously Presented) The input detection system as recited in Claim 11, wherein said control circuit is operable to detect when said cover is in said closed position and in an open position and is further operable to alter a detection threshold of said capacitive sensor component when said cover is in said open position.

16. (Previously Presented) The input detection system as recited in Claim 15, wherein said capacitive sensor component, responsive to said altered detection threshold, detects an indication above said second display component and said control system registers said indication as an input to said electronic device.

17. (Previously Presented) The input detection system as recited in Claim 11, wherein said cover further comprises:

a second sensor component operable to detect an indication in proximity to but not in contact with the surface of said second sensor component, wherein said indication is registered as an input to said electronic device.

18. (Previously Presented) The input detection system as recited in Claim 11, wherein said capacitive sensor component is further operable to detect said electronic device being handled and said control system, responsive to said handling, for actuating said electronic device.

19. (Previously Presented) An input detection system for an electronic device comprising:

a first display component;

a second display component disposed above said first display component;

an inductive sensor component operable to detect an indication in proximity to but not in contact with a surface of said electronic device and wherein said inductive sensor component is operable to differentiate between a first height and a second height of said indication above said second display component; and

a control circuit coupled to said inductive sensor component and operable to register said indication as an input to said electronic device at one of said first height and said second height, wherein an input at said first height corresponds to said first display component activated by said control circuit, and wherein an input at said second height corresponds to said second display component activated by said control circuit.

20-22. (Cancelled)

23. (Previously Presented) The input detection system as recited in Claim 19, wherein said control circuit is operable to detect when said cover is in said closed position and in an open position and is operable to alter a detection threshold of said inductive sensor component when said cover is in said open position.

24. (Previously Presented) The input detection system as recited in Claim 23, wherein said inductive sensor component, responsive to said altered detection threshold, detects an indication above said second display component and said control system registers said indication as an input to said electronic device.

25. (Previously Presented) The input detection system as recited in Claim 19, wherein said cover further comprises:

a second sensor component operable to detect an indication in proximity to but not in contact with the surface of said second sensor component, wherein said indication is registered as an input to said electronic device.

26. (New) The input detection system as recited in Claim 1, wherein said system further comprises:

a cover coupled to said electronic device by a hinge; and  
wherein said second display component is disposed within said cover having sufficient transparency to permit viewing of said first display component when said cover is in a closed position and wherein said second display component is disposed above said first display component.

27. (New) The input detection system as recited in Claim 26, wherein said sensor is operable to detect an indication above said second display component when said cover is in a closed position above said first display component.

28. (New) The input detection system as recited in Claim 11, wherein said system further comprises:

a cover coupled to said electronic device by a hinge; and  
wherein said second display component is disposed within said cover having sufficient transparency to permit viewing of said first display component when said cover is in a closed position and wherein said second display component is disposed above said first display component.

29. (New) The input detection system as recited in Claim 28, wherein said sensor is operable to detect an indication above said second display component when said cover is in a closed position above said first display component.

30. (New) The input detection system as recited in Claim 19, wherein said system further comprises:

a cover coupled to said electronic device by a hinge; and  
wherein said second display component is disposed within said cover having sufficient transparency to permit viewing of said first display component when said cover is in a closed position and said second display component is disposed above said first display component.

31. (New) The input detection system as recited in Claim 30, wherein said sensor is operable to detect an indication above said second display component when said cover is disposed above said first display component.